










Keaton - Technical information

Tile collection performance based on industry standards.

<i>Technical Information</i>		8 x 10 in / 20 x 25 cm 10 x 16 in / 25 x 40 cm	13 x 13 in / 33 x 33 cm
	WATER ABSORPTION	ANSI / ISO - (%)	10% ≤ E ≤ 16% - P4 < 3%
	ABRASION RESISTANCE	ANSI / ISO	CLASS 0 CLASS 3
	SCRATCH HARDNESS	ANSI / ISO - (Mohs)	3 6
	BREAKING STRENGTH	ANSI - (lbf) ISO - (N)	>230 >1000 >250 >1100
	SHADE VARIATION		V1
	SLIP RESISTANCE	ANSI - DCOF (WET) ISO - R VALUE	MATTE N/A MATTE N/A MATTE <0.42 MATTE R(-)
	CHEMICAL RESISTANCE	ANSI / ISO	CLASS B CLASS A
	STAIN RESISTANCE	ANSI / ISO	CLASS B CLASS 4 CLASS A CLASS 5
	FROST RESISTANCE	ANSI / ISO	NOT RESISTANT

Test values are based on ANSI / ISO standards according to: ANSI A137.1 Non-Vitreous P4 Class, ISO 13006 - L - Group BIIIb - EN 14411 - L - Group BIIIb. Variances in test values can occur in different production lots.

Usage recommendations

Anatolia's recommendations for suitable applications.

<i>Usage Recommendations*</i>		8 x 10 in / 20 x 25 cm 10 x 16 in / 25 x 40 cm	13 x 13 in / 33 x 33 cm		
APPLICATION		WALL	FLOOR	WALL	FLOOR
INTERIOR	RESIDENTIAL	•		•	•
	COMMERCIAL	•		•	
	HEAVY COMMERCIAL				
EXTERIOR	RESIDENTIAL / COMMERCIAL				

* These recommendations are not defined by ANSI/ISO standards.